


Spiral Wire Double Bolt Clamps

R-Power Band (for right-handed hose)

Structure (Cross-Section View)




Sizes

Item No.	Range of Use (mm)	W (mm)	φd (mm)	Applicable Hose	Applicable Hose Size (φ)
RP-38	50-40	50	5	WR	38
RP-50M	60-50	50	5	WR	50
RP-65M	73-58	50	5	WA, WS, WR	65
RP-75M	87-72	60	7	WT, WA, WS, WR, A/R W	75
RP-90	100-85	60	7	WT, WA, A/R W	90
RP-100A	118-98	60	7	WT, WA, WS, WR, A/R W	100
RP-115	132-112	60	9		115
RP-125M	143-123	70	9	WT, WA, WS, WR, A/R W	125
RP-150A	173-148	70	9	WT, WA, WS, WR, A/R W	150
RP-200	229-199	80	9	WT, WA, WS, WR	200
RP-250	285-245	90	9	WS, WR	250
RP-300	340-300	90	9	WS, WR	300

* A/R : Abrasion Resistant.

L-Power Band (for left-handed hose)




Sizes

Item No.	Range of Use (mm)	W (mm)	φd (mm)	Applicable Hose	Applicable Hose Size (φ)
LP-38	50-40	50	5		38
LP-50M	60-50	50	5		50
LP-65M	73-58	50	5	Antistatic W	65
LP-75M	87-72	60	7	Antistatic W	75
LP-90	100-85	60	7	Antistatic W	90
LP-100A	118-98	60	7	Antistatic W	100
LP-115	132-112	60	9	WT	115
LP-125M	143-123	70	9		125
LP-150A	173-148	70	9		150
LP-200	229-199	80	9		200
LP-250	285-245	90	9		250
LP-300	340-300	90	9		300

Breeze High Torque Band

Structure (Cross-Section View)




Sizes

Item No.	Range of Use (mm)	Applicable Hose	
		Item Name	Size
HTM350LB/75	70 ~ 92	F-3, E, A/R E	75
HTM500LB/100	108 ~ 130	F-3, E, A/R E	100
HTM600LB/125	133 ~ 156	F-3, E, A/R E	125
HTM700LB/150	159 ~ 191	F-3, E, A/R E	150

* A/R : Abrasion Resistant.

Tridon Band

Structure (Cross-Section View)



Sizes

Item No.	Range of Use (mm)	Cuff Size of Applicable Duct	Applicable Hose			
			Item Name	Size	Item Name	Size
8	11-25	16				
10	14-27	19	F-3	19		
12	14-32	25	F-3	25		
16	17-38		SF, Oil Resistant F	25		
20	19-44	32	F-3, E, SF, Oil Resistant F	32		
24	27-51	38	F-3, E, SF, Oil Resistant F, AP	38		
28	33-57		E	45		
32	40-63	50	E	48.6	V, F-3, E, SF, Oil Resistant F, AP	50
36	46-70					
40	52-76	65	V type	65		
44	59-82					
48	65-89	75	V type, AP type	75		
56	78-101	90	V type	90		
60	84-108					
64	64-114	100	V type, AP type	100		
72	76-127					
84	95-146	125	V type, AP type	125		
88	102-152					
96	114-165	150	V type	150		
104	127-178		AP type	150		
128	155-216		V type	175	V type	200
152	204-253	200	AP type	200		
188	260-311	300	V type	275	V type	300